

SKF PCZ 2816 E plain bearings

YOU'LL FIND AN EXTENSIVE 90x190x43 Size (mm) 190 Outer Diameter (mm) SELECTION 90 Bore Diameter (mm) OF SKF PCZ 2816 E plain bearings FOR SALE.

| | |
|-------------------------------|------------|
| Size (mm) | 90x190x43 |
| Bore Diameter (mm) | 90 |
| Outer Diameter (mm) | 190 |
| Width (mm) | 43 |
| d | 90 mm |
| D | 190 mm |
| B | 43 mm |
| C | 43 mm |
| r min. | 3 mm |
| da min. | 104 mm |
| da max | 115 mm |
| Da min | 152 mm |
| Da max. | 176 mm |
| ra max. | 2,5 mm |
| Weight | 6,1 Kg |
| Basic dynamic load rating (C) | 330 kN |
| Basic static load rating (C0) | 450 kN |
| (Grease) Lubrication Speed | 2600 r/min |
| (Oil) Lubrication Speed | 3400 r/min |
| Calculation factor (e) | 0,24 |
| Calculation factor (Y0) | 2,8 |
| Calculation factor (Y2) | 4,3 |
| Inventory | 0.0 |

| | |
|---------------------------|--|
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 6.2 |
| EAN | 0029176410956 |
| Product Group | B04311 |
| Internal Clearance | C0-Medium |
| Mounting Method | Shaft Mount |
| Rolling Element | Spherical Roller Bearing |
| Bore Profile | Straight |
| Cage Material | Steel |
| Enclosure | Open |
| Number of Rows of Rollers | Double Row |
| Relubricatable | Yes |
| Withdrawal Sleeve | Not Applicable |
| Inch – Metric | Metric |
| Long Description | 90MM Straight Bore; 190MM Outside Diameter; 43MM Width; C0-Medium Clearance; Shaft Mount; Double Row |
| UNSPSC | 31171510 |
| Harmonized Tariff Code | 84823080 |
| Noun | Bearing |
| Keyword String | Spherical |
| Manufacturer Item Number | 21318EAE4 |
| Weight / LBS | 0 |
| Adapter Part Number | Not Applicable Inch Not Applicable Millimeter |
| Outside Diameter | 7.48 Inch 190 Millimeter |
| Bore | 3.543 Inch 90 Millimeter |
| Width | 1.693 Inch 43 Millimeter |

| | |
|------------|-------------|
| Y3 | 2.9 |
| hidYobi | 21318EAE4 |
| LangID | 1 |
| Y1 | 2.9 |
| D_ | 190 |
| Y2 | 4.3 |
| Macha rpm | 4500 |
| B_ | 43 |
| da min | 104 |
| hidTable | ecat_NSSPHR |
| Oil rpm | 3600 |
| Y0 | 2.8 |
| mass | 6.1 |
| GRS rpm | 2800 |
| ra | 2.5 |
| TSR rpm | 3600 |
| C0 | 450 |
| DE_ | 155.103 |
| X0 | 1 |
| Prod_Type3 | SRB_CTB_CB |
| X1 | 1 |
| X2 | 0.67 |
| SIR | 17.22 |
| e | 0.24 |
| DA_ | 19.3 |
| bomp | 21318EAE4 |
| Z_ | 20 |
| ALP2 | 55 |
| ALP1 | 8 |

| | |
|---------|-----------|
| ALP3 | 0 |
| D_a max | 176 |
| D_a min | 152 |
| yobi | 21318EAE4 |
| HPS | HPS |
| ALPHA_ | 0.156 |
| SDM_ | 136.036 |
| r | 3 |
| KBRG | 2328 |
| SBRG | 3 |
| DI_ | 116.969 |