

SKF SILR 80 ES plain bearings

The online SKF SILR 80 ES plain bearings parts store gives you immediate access to a selection of more than 1.4 million 8 ° misalignment angle: new, 1000 lbf axial static load capacity: used, remanufactured.

| | |
|------------------------------|---------------------------------------------------------------------------------------------------------------|
| d | 0.2500 in |
| axial static load capacity: | 1000 lbf |
| misalignment angle: | 8 ° |
| operating temperature range: | Max 250 °F |
| shank thread length: | 0.7500 in |
| head diameter: | 0.8060 in |
| rod end type: | Female Threaded |
| head width: | 0.3370 in |
| shank thread size: | 5/16-24 |
| ball width: | 0.4370 in |
| thread direction: | Right Hand |
| length to ball center: | 1.4690 in |
| grade: | Military |
| overall height: | 1.8720 in |
| thread type: | UNJF-3B |
| standards met: | SAE-AS81935, SAE-AMS-QQ-P-416 Type 1 Class 2, SAE-AMS-H-6875, SAE-AMS-H-7199, ASTM-E-1444, SAE-AS818 |
| lubrication type: | Self-Lubricating |
| series: | Heim® |
| housing material: | 4340 Alloy Steel |
| manufacturer product page: | Click here |

| | |
|------------------------------|----------------------------|
| ball material: | 440 C Stainless Steel |
| Weight | 0.08 lbs |
| race material: | 17-4 PH Heat Treated, PTFE |
| manufacturer upc number: | 637400183172 |
| radial static load capacity: | 4860 lbf |