

SKF SYJ 50 KF+HA 2310 bearing units

SKF SYJ 50 KF+HA 2310 bearing units Industries 55 Outer Diameter (mm) and Applications ? We 35x55x10 Size (mm) sell discount online as well as cheap machinery parts.

Size (mm)	35x55x10
Bore Diameter (mm)	35
Outer Diameter (mm)	55
Width (mm)	10
d	35 mm
D	55 mm
B	10 mm
C	10 mm
r min.	0,6 mm
da min.	39 mm
da max	40 mm
Da max.	51 mm
ra max.	0,6 mm
Weight	0,074 Kg
Basic dynamic load rating (C)	9,55 kN
Basic static load rating (C0)	6,85 kN
Reference speed	7 100 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.073
EAN	4547359006773

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	35MM Bore; 55MM Outside Diameter; 10MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6907LLU/2AS
Weight / LBS	0.161
Bore	1.378 Inch 35 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
Outside Diameter	2.165 Inch 55 Millimeter
bore diameter:	35 mm
precision rating:	ISO Class 0
outside diameter:	55 mm
finish/coating:	Uncoated
overall width:	10 mm
bearing material:	High Carbon Chrome Steel

bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	10 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	10 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	7100 rpm
internal clearance:	CN
fillet radius:	0.6 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	7100 RPM
dynamic load capacity:	9550 N
series:	69
static load capacity:	6850 N
manufacturer product page:	Click here