SKF SYNT 55 FW bearing units

What is 11.8125 in overall length: the best place to 2.9375 in d buy SKF SYNT 55 FW bearing units online? 3-3/16 in base width: Manufacturing Service .

| base width:3-3/16 inoverall length:11.8125 inexpansion type:Non-Expansion Bearing (Fixed)overall height:6.3125 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Clearance/Non-Contactbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | | 1 1 |
|---|-------------------------------|-------------------------------|
| overall length:11.8125 inexpansion type:Non-Expansion Bearing (Fixed)overall height:6.3125 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Clearance/Non-Contactbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | d | 2.9375 in |
| expansion type:Non-Expansion Bearing (Fixed)overall height:6.3125 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Clearance/Non-Contactbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | base width: | 3-3/16 in |
| overall height:6.3125 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Clearance/Non-Contactbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | overall length: | 11.8125 in |
| finish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Clearance/Non-Contactbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:5000D7-13/16 to 9-3/4 in | expansion type: | Non-Expansion Bearing (Fixed) |
| mounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Clearance/Non-Contactbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:5000D7-13/16 to 9-3/4 in | overall height: | 6.3125 in |
| B4-7/8 inbearing type:Spherical Rollerseal type:Clearance/Non-Contactbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | finish/coating: | Powder Coated |
| bearing type:Spherical Rollerseal type:Clearance/Non-Contactbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | mounting: | Four-Bolt Base |
| seal type:Clearance/Non-Contactbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | В | 4-7/8 in |
| bore type: Round radial dynamic load capacity: 46800 lb housing construction: Solid Pillow Block radial static load capacity: 55700 lb base to bore centerline: 3.1250 in maximum rpm: 2800 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Double Concentric Collar series: 5000 D 7-13/16 to 9-3/4 in | bearing type: | Spherical Roller |
| radial dynamic load capacity: 46800 lb housing construction: Solid Pillow Block radial static load capacity: 55700 lb base to bore centerline: 3.1250 in maximum rpm: 2800 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Double Concentric Collar series: 5000 D 7-13/16 to 9-3/4 in | seal type: | Clearance/Non-Contact |
| housing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | bore type: | Round |
| radial static load capacity: 55700 lb base to bore centerline: 3.1250 in maximum rpm: 2800 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Double Concentric Collar series: 5000 D 7-13/16 to 9-3/4 in | radial dynamic load capacity: | 46800 lb |
| base to bore centerline:3.1250 inmaximum rpm:2800 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | housing construction: | Solid Pillow Block |
| maximum rpm: 2800 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Double Concentric Collar series: 5000 D 7-13/16 to 9-3/4 in | radial static load capacity: | 55700 lb |
| housing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | base to bore centerline: | 3.1250 in |
| Iubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000D7-13/16 to 9-3/4 in | maximum rpm: | 2800 RPM |
| locking device: Double Concentric Collar series: 5000 D 7-13/16 to 9-3/4 in | housing material: | Cast Iron |
| series: 5000 D 7-13/16 to 9-3/4 in | lubrication type: | Lubrication Fitting |
| D 7-13/16 to 9-3/4 in | locking device: | Double Concentric Collar |
| | series: | 5000 |
| standards met: ANSI/ABMA STD 9-1990 | D | 7-13/16 to 9-3/4 in |
| | standards met: | ANSI/ABMA STD 9-1990 |