

SKF W 61906-2Z deep groove ball bearings

SKF W 61906-2Z deep groove ball bearings Deal TIMKEN
Manufacturer Name is your source for OEM and N/A Minimum Buy
Quantity accessories. We sell Genuine at discount prices. 0.0
Inventory

| | |
|---------------------------|----------------------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 48.63 |
| EAN | 0013992048776 |
| Product Group | B04144 |
| Number of Mounting Holes | 4 |
| Mounting Method | Clamp Collar |
| Housing Style | 4 Bolt Round Flange Block |
| Rolling Element | Cylindrical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Expansion |
| Mounting Bolts | 16 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | MSE311BX |
| Seals | Triple Lip Labyrinth |
| Housing Configuration | 2 Piece Split |
| Pilot Configuration | No Pilot |
| Inch – Metric | Inch |

| | |
|---------------------------------------|---|
| Long Description | 4 Bolt Round Flange Block; 3-11/16" Bore; 13.1" Bolt Circle; 2 Piece Split; Clamp Collar M |
| Other Features | Single Row Wide Inner Ring Medium Duty |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Flanged |
| Weight / LBS | 107.12 |
| d | 3.688 Inch 93.675 Millimeter |
| Bolt Spacing | 9.3 Inch 236.2 Millimeter |
| D | 3.626 Inch 92.1 Millimeter |
| Nominal Bolt Circle Diameter Round | 13.1 Inch 334 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Shaft Size | 3-11/16 in |
| Seal Type | Aluminium Triple Labyrinth |
| Bearing Type | Split Cylindrical Expansion Type |
| Support Type | Round Flange |
| Series Type | Medium Series |
| Bolt Size | 4 x M16 |
| Bearing – Housing – Seal | MSE311BXHATL |
| Bearing – Housing – Seal UPC | 013992061263 |
| Bearing UPC | 013992039194 |
| Dimension T | 15.0 in |
| Dimension R | 13.1 in |

| | |
|--------------------------|---|
| Dimension P | 0.9 in |
| Dimension H | 3.6 in |
| Dimension N | 10.875 in |
| Dimension V | 0.1 in |
| Dimension L | 6.5 in |
| Cr – Dynamic Load Rating | 87226 lbf |
| Cor – Static Load Rating | 110381 lbf |
| Maximum Speed | 2130 rpm |
| Note | This product line was formerly known as “Revolvo” |