SKF W619/6-2Z deep groove ball bearings

SKF W619/6-2Z deep groove ball bearings manufacturer and global supplier of reliable ball and roller ... SKF W619/6-2Z deep groove ball bearings Industries Products Manufacturing & Engineering and 0.0 Inventory Agricultural Bearings designed to meet the unique requirements of our targeted industries.

| Inventory | 0.0 |
|---------------------------|--------------------------|
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 96.25 |
| EAN | 0087796217317 |
| Product Group | M06288 |
| Number of Mounting Holes | 4 |
| Mounting Method | Tapered Adapter Sleeve |
| Housing Style | 4 Bolt Pillow Block |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 1 Inch |
| Relubricatable | Yes |
| Insert Part Number | 23036K |
| Seals | Triple Ring Labyrinth |
| Housing Configuration | 2 Piece Split |
| Inch — Metric | Inch |
| Other Features | Double Row |

| Long Description4 Bolt Pillow Block; 6-7/16" Bore; 6-11/16" Base to Center Height; Tapered Adapter SleeveUNSPSC31171511Harmonized Tariff Code8483.20.40.80NounBearingKeyword StringPillow BlockManufacturer Item NumberSAF 23036KWeight / LBS212Bolt Spacing Minimum17.375 Inch 441.325MillimeterB22.00 inNominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0.26Triple Seal ReqdLOR 148 | | |
|--|-------------------------------|---------------------------------|
| Height: Tapered Adapter SleeveUNSPSC31171511Harmonized Tariff Code8483.20.40.80NounBearingKeyword StringPillow BlockManufacturer Item NumberSAF 23036KWeight / LBS212Bolt Spacing Minimum17.375 Inch 441.325MillimeterB22.00 inNominal Bolt Center to Center8.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.7.3750 inStabilizing Ring 1 Reqd3SR-0.26 | Long Decemintion | 4 Bolt Pillow Block; 6-7/16" |
| UNSPSC31171511Harmonized Tariff Code8483.20.40.80NounBearingKeyword StringPillow BlockManufacturer Item NumberSAF 23036KWeight / LBS212Bolt Spacing Minimum17.375 Inch 441.325MillimeterB22.00 inNominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Long Description | |
| Harmonized Tariff Code8483.20.40.80NounBearingKeyword StringPillow BlockManufacturer Item NumberSAF 23036KWeight / LBS212Bolt Spacing Minimum17.375 Inch 441.325MillimeterB22.00 inNominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.SR-0.26 | | |
| NounBearingKeyword StringPillow BlockManufacturer Item NumberSAF 23036KWeight / LBS212Bolt Spacing Minimum17.375 Inch 441.325MillimeterB22.00 inNominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.3.750 in | UNSPSC | 31171511 |
| Keyword StringPillow BlockManufacturer Item NumberSAF 23036KWeight / LBS212Bolt Spacing Minimum17.375 Inch 441.325MillimeterB22.00 inNominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.0375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0.26 | Harmonized Tariff Code | 8483.20.40.80 |
| Manufacturer Item NumberSAF 23036KWeight / LBS212Bolt Spacing Minimum17.375 Inch 441.325MillimeterB22.00 inNominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Noun | Bearing |
| Weight / LBS212Bolt Spacing Minimum17.375 Inch 441.325MillimeterB22.00 inNominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0.26 | Keyword String | Pillow Block |
| Bolt Spacing Minimum17.375 Inch 441.325MillimeterB22.00 inNominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Manufacturer Item Number | SAF 23036K |
| B22.00 inNominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Weight / LBS | 212 |
| Nominal Bolt Center to Center18.3 Inch 464.8 MillimeterActual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Bolt Spacing Minimum | 17.375 Inch 441.325Millimeter |
| Actual Bolt Center to Center0 Inch 0MillimeterD2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | В | 22.00 in |
| D2.6250 ind6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Nominal Bolt Center to Center | 18.3 Inch 464.8 Millimeter |
| d6.438 Inch 163.525 MillimeterBolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Actual Bolt Center to Center | 0 Inch OMillimeter |
| Bolt Spacing Maximum19.25 Inch 488.95MillimeterDiameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | D | 2.6250 in |
| Diameter S-16 7/16 inAdapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | d | 6.438 Inch 163.525 Millimeter |
| Adapter Assembly Number1SNW-3036 x 6-7/16Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Bolt Spacing Maximum | 19.25 Inch 488.95Millimeter |
| Housing Only2SAF036KA6.6875 inC6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Diameter S-1 | 6 7/16 in |
| A 6.6875 in C 6.250 in F 3.75 in H 13.3125 in Bolt Hole Length 1.9375 in Bolt Hole Width 1.000 in E Max. 19.2500 in E Min. 17.3750 in Stabilizing Ring 1 Reqd3 SR-0-26 | Adapter Assembly Number1 | SNW-3036 x 6-7/16 |
| C6.250 inF3.75 inH13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Housing Only2 | SAF036K |
| F 3.75 in H 13.3125 in Bolt Hole Length 1.9375 in Bolt Hole Width 1.000 in E Max. 19.2500 in E Min. 17.3750 in Stabilizing Ring 1 Reqd3 SR-0-26 | A | 6.6875 in |
| H13.3125 inBolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | С | 6.250 in |
| Bolt Hole Length1.9375 inBolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | F | 3.75 in |
| Bolt Hole Width1.000 inE Max.19.2500 inE Min.17.3750 inStabilizing Ring 1 Reqd3SR-0-26 | Н | 13.3125 in |
| E Max. 19.2500 in E Min. 17.3750 in Stabilizing Ring 1 Reqd3 SR-0-26 | Bolt Hole Length | 1.9375 in |
| E Min. 17.3750 in Stabilizing Ring 1 Reqd3 SR-0-26 | Bolt Hole Width | 1.000 in |
| Stabilizing Ring 1 Reqd3 SR-0-26 | E Max. | 19.2500 in |
| | E Min. | 17.3750 in |
| Triple Seal Reqd LOR 148 | Stabilizing Ring 1 Reqd3 | SR-0-26 |
| | Triple Seal Reqd | LOR 148 |

| Assembly Weight | 212.0 lb |
|-------------------------|------------------|
| Bolt Holes | 4 |
| Full Timken Part Number | SAF23036K |
| Seal Type | Triple Ring Seal |