

# SKF WBB1-8701 R deep groove ball bearings

SKF WBB1-8701 R deep groove ball bearings Engineering Calculator , Manufacturing Service . Get 80 mm da Your Free.

da	80 mm
db	92.075 mm
dc	76.2 mm
Da	140 mm
Ca	42.799 mm
A1	88.9 mm
A2	133.35 mm
S	4.763 mm
ba	34.131 mm
H	174.625 mm
H1	88.9 mm
H2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
J1	53.975 mm
L	330.2 mm
N1	19.05 mm
R1	53.181 mm
R2	21.431 mm
RG	3/8 NPT
PG	1/8 NPT
h	31.75 mm
Housing	FSAFS 216

Bearing	22216 E
Lock nut	AN 16
Lock washer	W 16
Stabilizing ring	SR-16-13
Labyrinth ring (db shaft position)	LOR 82
PosiTrac Plus contact element (db shaft position)	B10724-79
Labyrinth ring (dc shaft position)	LOR 54
PosiTrac Plus contact element (dc shaft position)	B10724-53
End plug (suffix Y)	EPR 9
Max. speed for PosiTrac Plus seal	1450 r/min
P60°	138 kN
P90°	82.7 kN
P120°	49.8 kN
P150°	44.5 kN
P180°	52.5 kN
Pa	33.8 kN
Mass pillow block	20 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	87.885 g