SL183012 INA 60x95x26mm Other Features Full Complement | 2 Rib Inner Ring | 1 Rib Outer Ring with Retaining Ring | 0perating Temperature From -30 to 120 Deg Cylindrical roller bearings

| Bearing number | SL183012 |
|-----------------------|---|
| Size (mm) | 60x95x26 |
| Brand | INA |
| Bore Diameter (mm) | 60 |
| Outer Diameter (mm) | 95 |
| Width (mm) | 26 |
| d | 60 mm |
| D | 95 mm |
| В | 26 mm |
| D_1 | 82.1 mm |
| d ₁ | 71.7 mm |
| E | 86.74 mm |
| r _{min} | 1.1 mm |
| S | 2 mm / Axial displacement |
| m | 0.69 kg / Weight |
| C _r | 123000 N / Dynamic load rating (radial) |

| C ₀ r | 143000 N / Static load rating (radial) |
|------------------------------|--|
| C _{ur} | 23700 N / Fatigue limit load. radial |
| n_{\scriptscriptstyleG} | 4350 1/min / Limiting speed |
| Category | Cylindrical Roller Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.83 |
| EAN | 4012802272345 |
| Product Group — BDI | B04144 |
| Bore Profile | Straight |
| Cage Material | None |
| Precision Class | RBEC 1 ISO PO |
| Number of Rows of Rollers | Single Row |
| Separable | No |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | No |
| Relubricatable | Yes |
| Inch — Metric | Metric |
| Other Features | Full Complement 2 Rib Inner Ring 1 Rib Outer Ring with Retaining Ring Operating Temperature From -30 to 120 Deg |

| Straight Bore Profile; Diameter; 26MM Width; |
|--|
| O PO; Single Row; Not le; No Snap Ring; le; CO-Medium Internal nce; No Retainer |
| cal Roller Bearing |
| 31171547 |
| 182.50.00.00 |
| Bearing |
| ://www.ina.com |
| SL183012 |
| 1.822 |
| ch 95 Millimeter |
| ch 26 Millimeter |
| ch 60 Millimeter |
| |