

SL183012 INA 60x95x26mm Other Features Full Complement | 2 Rib Inner Ring | 1 Rib Outer Ring with Retaining Ring | Operating Temperature From -30 to 120 Deg Cylindrical roller bearings

| | |
|---------------------|---|
| Bearing number | SL183012 |
| Size (mm) | 60x95x26 |
| Brand | INA |
| Bore Diameter (mm) | 60 |
| Outer Diameter (mm) | 95 |
| Width (mm) | 26 |
| d | 60 mm |
| D | 95 mm |
| B | 26 mm |
| D ₁ | 82.1 mm |
| d ₁ | 71.7 mm |
| E | 86.74 mm |
| r _{min} | 1.1 mm |
| s | 2 mm / Axial displacement |
| m | 0.69 kg / Weight |
| C _r | 123000 N / Dynamic load rating (radial) |

| | |
|------------------------------|--|
| C_{0r} | 143000 N / Static load rating (radial) |
| C_{ur} | 23700 N / Fatigue limit load. radial |
| n_G | 4350 1/min / Limiting speed |
| Category | Cylindrical Roller Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.83 |
| EAN | 4012802272345 |
| Product Group – BDI | B04144 |
| Bore Profile | Straight |
| Cage Material | None |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | No |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | No |
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | Full Complement 2 Rib Inner Ring 1 Rib Outer Ring with Retaining Ring Operating Temperature From -30 to 120 Deg |

| | |
|--------------------------|--|
| Long Description | 60MM Bore; Straight Bore Profile; 95MM Outside Diameter; 26MM Width; RBEC 1 ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; No Retainer |
| Category – BDI | Cylindrical Roller Bearing |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer URL | http://www.ina.com |
| Manufacturer Item Number | SL183012 |
| Weight / LBS | 1.822 |
| Outside Diameter | 3.74 Inch 95 Millimeter |
| Width | 1.024 Inch 26 Millimeter |
| Bore | 2.362 Inch 60 Millimeter |