

# Slewing Ring with Limited Clearance Ungeared

## 250.15.0475.013

What is the best place to buy Slewing Ring with Limited Clearance Ungeared 250.15.0475.013 online? 350x280x33 Size (mm) Manufacturing Service .

Size (mm)	350x280x33
Bore Diameter (mm)	350
Outer Diameter (mm)	280
Width (mm)	33
d	280 mm
D	350 mm
B	33 mm
d1	302 mm
D1	327 mm
r1,2 – min.	2 mm
da – min.	289 mm
Da – max.	341 mm
ra – max.	2 mm
Basic dynamic load rating – C	138 kN
Basic static load rating – C0	200 kN
Fatigue load limit – Pu	4.8 kN
Reference speed	3400 r/min
Limiting speed	2200 r/min
Calculation factor – kr	0.015
Calculation factor – f0	17.3

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	6.548
EAN	7316576610608
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	280MM Bore; 350MM Outside Diameter; 33MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	61856
Weight / LBS	14.423
Bore	11.024 Inch   280 Millimeter
Outside Diameter	13.78 Inch   350 Millimeter
Outer Race Width	1.299 Inch   33 Millimeter
bore diameter:	280 mm
static load capacity:	200 kN

outside diameter:	350 mm
precision rating:	Not Rated
overall width:	33 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	33 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	2 mm
snap ring included:	With Snap Ring
maximum rpm:	2200 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	138 kN
d1 ≈	302 mm
D1 ≈	327 mm
r1,2 min.	2 mm
da min.	289 mm
Da max.	341 mm
ra max.	2 mm
Basic dynamic load rating C	138 kN
Basic static load rating C0	200 kN
Fatigue load limit Pu	4.75 kN
Calculation factor kr	0.015
Calculation factor f0	17.3
Mass bearing	6.27 kg