

SNFA BS 60/120 /S 7P62U thrust ball bearings

We work closely with our SNFA BS 60/120 /S 7P62U thrust ball bearings manufacturing partners 72×31.75×42.9 Size (mm) to bring the best value to customers. 31,75 Outer Diameter (mm)

Size (mm)	72×31.75×42.9
Bore Diameter (mm)	72
Outer Diameter (mm)	31,75
Width (mm)	42,9
d	31.75 mm
D	72 mm
B	42.9 mm
C	19 mm
d1	46.1 mm
B4	6 mm
s1	25.4 mm
r1,2 – min.	1 mm
Basic dynamic load rating – C	25.5 kN
Basic static load rating – C0	15.3 kN
Limiting speed	80 r/min
Limiting temperature – T	250 °C
Mass bearing	0.52 kg
Grub (set) screw – G2 – 5/16-24 UNF	5/1624 UNF
Hexagonal key size for grub screw – H	3.969 mm
d1 ≈	46.1 mm
r1,2 min.	1 mm
Basic dynamic load rating C	25.5 kN

Basic static load rating C0	15.3 kN
Limiting temperature T max.	250 °C
Grub (set) screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m