

SNFA E 290 /S 7CE1 angular contact ball bearings

170 Million used SNFA E 290 /S 7CE1 angular contact ball bearings instantly searchable. Shop our 0.0 Inventory large selection of N/A Minimum Buy Quantity parts based on TIMKEN Manufacturer Name brand, price, description, and location. Order the with stock ...

| | |
|---------------------------|------------------------------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 61.25 |
| EAN | 0087796302716 |
| Product Group | B04144 |
| Bore Profile | Straight |
| Cage Material | Brass |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | Inner Ring – Both Sides |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | Yes |
| Relubricatable | Yes |
| Inch – Metric | Metric |

| | |
|--|---|
| Other Features | Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID |
| Long Description | 340MM Bore; Straight Bore Profile; 520MM Outside Diameter; 82MM Width; Brass Cage Material; RBEC 1 |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer Item Number | NU1068MA |
| Weight / LBS | 134.9 |
| B | 3.228 Inch 82 Millimeter |
| D | 20.472 Inch 520 Millimeter |
| d | 13.386 Inch 340 Millimeter |
| Design Units | METRIC |
| Bearing Weight | 64.200 Kg |
| Type | NU |
| Tapered Bore | N |
| d – Bore | 340.000 mm |
| D – Outer Diameter | 520.000 mm |
| C – Inner Ring Width | 82 mm |
| B – Outer Ring Width | 82 mm |
| C0 – Static Radial Rating | 1800000 N |
| C – Dynamic Radial Rating ¹ | 1240000 N |
| Reference Thermal Speed Rating (Grease) | 1000 |
| Reference Thermal Speed Rating (Oil) ² | 1200 |
| Cg – Geometry Factor ³ | 0.1835 |

| | |
|---|------------|
| R – Inner Ring To Clear Radius ⁴ | 4.000 mm |
| r – Outer Ring To Clear Radius ⁵ | 4.000 mm |
| da – Inner Ring Backing Diameter | 358.000 mm |
| Da – Outer Ring Backing Diameter | 502.000 mm |