

SNFA SEA120 /NS 7CE1 angular contact ball bearings

Shop SNFA SEA120 /NS 7CE1 angular contact ball bearings huge online discount 0.0 Inventory SKF Manufacturer Name inventory. and Import machinery parts your car needs with Free Shipping N/A Minimum Buy Quantity and Free Extended Warranty.

| | |
|----------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 78.07 |
| EAN | 7316576616563 |
| Product Group | B04311 |
| Rolling Element | Spherical Roller Bearing |
| Self Aligning | Yes |
| Component Description | Roller Assembly plus Raceways |
| Thrust Bearing | Yes |
| Single or Double Direction | Single Direction |
| Banded | No |
| Cage Material | Steel |
| Precision Class | ABEC 1 ISO P0 |
| Other Features | Single Row Window Type Cage |
| Long Description | 320MM Bore 1; 391MM Bore 2; 500MM Outside Diameter; 109MM Height; Spherical Roller Bearing; Single D |
| Inch – Metric | Metric |
| UNSPSC | 31171507 |
| Harmonized Tariff Code | 8482.30.00.40 |

| | |
|-------------------------------------|------------------------------|
| Noun | Bearing |
| Keyword 3 | Spherical |
| Keyword String | Thrust Roller Spherical |
| Manufacturer Item Number | 29364 E |
| Weight / LBS | 171.961 |
| Bore 1 | 12.598 Inch 320 Millimeter |
| Height | 4.291 Inch 109 Millimeter |
| Bore 2 | 15.394 Inch 391 Millimeter |
| D | 500 mm |
| Overall Height with Aligning Washer | 0 Inch 0 Millimeter |
| bore diameter: | 320 mm |
| operating temperature range: | Maximum of +392 °F |
| outside diameter: | 500 mm |
| maximum rpm: | 1200 RPM |
| overall width: | 109 mm |
| separable type: | Non-Separable |
| cage material: | Steel |
| fillet radius: | 4 mm |
| static load capacity: | 11200 kN |
| series: | 293 |
| dynamic load capacity: | 3350 kN |
| d | 320 mm |
| H | 109 mm |
| d1 ≈ | 454 mm |
| D1 ≈ | 391 mm |
| B | 68 mm |
| B1 | 97.8 mm |
| C | 53 mm |

| | |
|---|------------|
| s | 180 mm |
| r _{1,2} min. | 5 mm |
| d _a min. | 405 mm |
| d _{b1} max. | 332 mm |
| d _{b2} max. | 347 mm |
| D _a max. | 442 mm |
| r _a max. | 4 mm |
| Basic dynamic load rating C | 3350 kN |
| Basic static load rating C ₀ | 11200 kN |
| Fatigue load limit P _u | 1000 kN |
| Reference speed | 750 r/min |
| Limiting speed | 1200 r/min |
| Minimum axial load factor A | 12 |
| Mass bearing | 78 kg |