

SNFA VEX 10 7CE1 angular contact ball bearings

LET OUR SNFA VEX 10 7CE1 angular contact ball bearings EXPERTS GET YOU THE N/A Minimum Buy Quantity PARTS 0.0 Inventory YOU NSK Manufacturer Name NEED.

| | |
|----------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight | 1.56 |
| EAN | 0029176586187 |
| Product Group | B04270 |
| Enclosure | Open |
| Precision Class | ABEC 7 ISO P4 |
| Material – Ball | Steel |
| Number of Bearings | 2 (1 Pair) |
| Contact Angle | 25 Degree |
| Preload | Light |
| Raceway Style | 1 Rib Outer Ring |
| Cage Material | Phenolic |
| Rolling Element | Ball Bearing |
| Mounting Arrangement | Duplex-Universal |
| Flush Ground | Yes |
| Inch – Metric | Metric |
| Other Features | Single Row Angular Contact Bore and OD are Exclusive All Others are ISO 4 |

| | |
|-------------------------------|--|
| Long Description | 60MM Bore; 110MM Outside Diameter; 44MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact Ball |
| Manufacturer Item Number | 7212A5TRDULP4Y |
| Weight / LBS | 3.439 |
| B | 1.732 Inch 44 Millimeter |
| d | 2.362 Inch 60 Millimeter |
| D | 4.331 Inch 110 Millimeter |
| bore diameter: | 60 mm |
| radial dynamic load capacity: | 6300 kgf |
| outside diameter: | 110 mm |
| radial static load capacity: | 4950 kgf |
| overall width: | 22 mm |
| maximum rpm: | 9000 RPM |
| contact angle: | 25 ° |
| cage material: | Synthetic Resin |
| internal clearance: | C0 |
| finish/coating: | Uncoated |
| ball screw application: | Not for Ball Screws |
| outer ring width: | 22 mm |
| closure type: | Open |
| fillet radius: | 1.5 mm |
| precision rating: | ABEC 7 (ISO Class 4) |
| series: | 72 |