

SNR 31304/2T tapered roller bearings

What is 0.0 Inventory SNR 31304/2T tapered roller bearings in mechanical engineering? Manufacturing Service . N/A Minimum Buy Quantity Upload your CAD file for an instant.

| | |
|---------------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 46.308 |
| EAN | 0883450306317 |
| Product Group | M06288 |
| Number of Mounting Holes | 6 |
| Mounting Method | Concentric Collar |
| Housing Style | 6 Bolt Round Flange Cartridge |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Steel |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 7/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | 22226 |
| Seals | Triple Lip Viton |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | With Pilot |
| Inch – Metric | Metric |
| Long Description | 6 Bolt Round Flange Cartridge; 130MM Bore; 325.1MM Bolt Circle; 161.925MM Bolt Spacing; 1 Piece Soli |

| | |
|------------------------------------|---|
| Other Features | Double Row Double Collar With Set Screw |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Flanged |
| Weight / LBS | 102 |
| Cartridge Pilot Diameter | 11 Inch 279.4 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Nominal Bolt Circle Diameter Round | 12.8 Inch 325.1 Millimeter |
| Bolt Spacing | 6.375 Inch 161.925 Millimeter |
| D | 7.44 Inch 188.976 Millimeter |
| d | 5.118 Inch 130 Millimeter |