

SNR 6004HT200 deep groove ball bearings

Advance SNR 6004HT200 deep groove ball bearings is your source for quality 20x42x8 Size (mm) and accessories. shop online 42 Outer Diameter (mm) for home delivery or pick up in one of our 10000 .

Size (mm)	20x42x8
Bore Diameter (mm)	20
Outer Diameter (mm)	42
Width (mm)	8
d	20 mm
D	42 mm
B	8 mm
C	8 mm
r min.	0,3 mm
da min.	22 mm
Da max.	40 mm
ra max.	0,3 mm
Weight	0,048 Kg
Basic dynamic load rating (C)	7,9 kN
Basic static load rating (C0)	4,45 kN
(Grease) Lubrication Speed	18 000 r/min
(Oil) Lubrication Speed	20 000 r/min
Inventory	3.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.05

EAN	0029176059391
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 42MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No F
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.11
Outside Diameter	1.654 Inch 42 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
Bore	0.787 Inch 20 Millimeter
bore diameter:	20 mm
static load capacity:	4450 N
outside diameter:	42 mm
precision rating:	Not Rated
overall width:	8 mm
finish/coating:	Uncoated
bore type:	Round

cage material:	Steel
closure type:	Open
outer ring width:	8 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
internal clearance:	C0
maximum rpm:	20000 RPM
dynamic load capacity:	7900 N
series:	160
SRI	2.88
hidYobi	16004
LangID	1
D_	42
SREX	0.015
B_	8
da min	22
hidTable	ecat_NSRDGB
Oil rpm	20000
SRE	2.88
mass	0.048
GRS rpm	18000
ra	0.3
SRIX	0.015
D_a	40
SRIN	-0.015
C0	4.45
fo	14.5
SREN	-0.015
DE_	36.556

Prod_Type3	DGBB_SR_OT
DA_	5.556
bomp	0
Z_	10
yobi	16004
C_conv	7900
ALPHA_	0
SDM_	31
r	0.3
KBRG	6101
SBRG	0
DI_	25.444