

SNR 6207F600 deep groove ball bearings

Can't find 40x36x16 Size (mm) what you're looking 36 Outer Diameter (mm) for SNR 6207F600 deep groove ball bearings ? Our expert Representatives be in contact 40 Bore Diameter (mm) with you shortly!

Size (mm)	40x36x16
Bore Diameter (mm)	40
Outer Diameter (mm)	36
Width (mm)	16
d	40 mm
A	36 mm
A1	16 mm
A3 – H14	3.2 mm
B	49.2 mm
B4	8 mm
Da – H11	88.9 mm
Db1	97 mm
Db2	100 mm
J	144 mm
H	16 mm
L	100 mm
s1	30.2 mm
T	51.2 mm
J6	116 mm
J7	16 mm
N4	2 mm

DN	6.5 mm
SWN	7 mm
GN – 1/4-28 SAE-LT	1/428 SAELT
RG – 1/4-28 UNF	1/428 UNF
R1	21.5 mm
Rα	45 °
Basic dynamic load rating – C	30.7 kN
Basic static load rating – C0	19 kN
Fatigue load limit – Pu	0.8 kN
Limiting speed	4800 r/min
Mass bearing unit	1.5 kg
Thread – G2	M8x1
Hexagonal key size for grub screw – H	4 mm
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.55
EAN	7316570225693
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	14 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 208-2F

Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Metric
Long Description	2 Bolt Flange Block; 40MM Bore; 144MM Bolt Circle; 144MM Bolt Spacing; 1 Piece Solid; Set Screw Moun
Other Features	Single Row Wide Inner Race Open End Has Flinger
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FYTJ 40 TF
Weight / LBS	3.42
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Length Thru Bore	1.937 Inch 49.2 Millimeter
Bolt Spacing	5.669 Inch 144 Millimeter
Nominal Bolt Circle Diameter Round	5.7 Inch 144 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Bore	1.575 Inch 40 Millimeter
Housing material	Cast iron
Da	88.9 mm
A3	3.2 mm
N	16 mm
RG	1/4-28 UNF

Rα	45 °
GN	1/4-28 SAE-LT
Basic dynamic load rating C	30.7 kN
Basic static load rating C0	19 kN
Fatigue load limit Pu	0.8 kN
Thread grub screw G2	M8x1
Hexagonal key size for grub screw N	4 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	14 mm
Recommended diameter for attachment bolts, inch G	0.5625 in
Housing	FYTJ 508
Bearing	YAR 208-2F