SNR 7018HVDUJ74 angular contact ball bearings

Our highly-skilled and factory-trained service experts have the resources 1.6875 in d to help you with all your SNR 7018HVDUJ74 angular contact ball bearings needs — including routine 5139 lb radial static load capacity: maintenance, major repairs, warranty service, and equipment inspections.

d1.6875 inradial static load capacity:5139 lbD5.8438 inseal type:Contact SealB7.0625 inlength through bore:3 inbore type:Roundoperating temperature range:-20 to +200 °Fduty type:Standard Dutyfinish/coating:Uncoatedmounting type:Two-Bolt Flangemaximum rpm:3000 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Skwezloc Collarseries:SFTMH-Texpansion type:2-111radial dynamic load capacity:7901 lbmanufacturer upc number:662461340691		
D5.8438 inseal type:Contact SealB7.0625 inlength through bore:3 inbore type:Roundoperating temperature range:-20 to +200 °Fduty type:Standard Dutyfinish/coating:Uncoatedmounting type:Two-Bolt Flangemaximum rpm:3000 RPMhousing material:Cast Ironlubrication type:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	d	1.6875 in
seal type: Contact Seal B 7.0625 in length through bore: 3 in bore type: Round operating temperature range: -20 to +200 °F duty type: Standard Duty finish/coating: Uncoated mounting type: Two-Bolt Flange maximum rpm: 3000 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Skwezloc Collar series: SFTMH-T expansion type: 2-111 radial dynamic load capacity: 7901 lb	radial static load capacity:	5139 lb
B7.0625 inlength through bore:3 inbore type:Roundoperating temperature range:-20 to +200 °Fduty type:Standard Dutyfinish/coating:Uncoatedmounting type:Two-Bolt Flangemaximum rpm:3000 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Skwezloc Collarseries:SFTMH-Texpansion type:2-111radial dynamic load capacity:7901 lb	D	5.8438 in
length through bore:3 inbore type:Roundoperating temperature range:-20 to +200 °Fduty type:Standard Dutyfinish/coating:Uncoatedmounting type:Two-Bolt Flangemaximum rpm:3000 RPMhousing material:Cast Ironlubrication type:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	seal type:	Contact Seal
bore type:Roundoperating temperature range:-20 to +200 °Fduty type:Standard Dutyfinish/coating:Uncoatedmounting type:Two-Bolt Flangemaximum rpm:3000 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	В	7.0625 in
operating temperature range:-20 to +200 °Fduty type:Standard Dutyfinish/coating:Uncoatedmounting type:Two-Bolt Flangemaximum rpm:3000 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	length through bore:	3 in
duty type:Standard Dutyfinish/coating:Uncoatedmounting type:Two-Bolt Flangemaximum rpm:3000 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	bore type:	Round
finish/coating: Uncoated mounting type: Two-Bolt Flange maximum rpm: 3000 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Skwezloc Collar series: SFTMH-T expansion type: Non-Expansion Bearing (Fixed) replacement bearing: 2-111 radial dynamic load capacity: 7901 lb	operating temperature range:	-20 to +200 °F
mounting type:Two-Bolt Flangemaximum rpm:3000 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	duty type:	Standard Duty
maximum rpm:3000 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	finish/coating:	Uncoated
housing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	mounting type:	Two-Bolt Flange
lubrication type:Lubrication Fittinglocking device:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	maximum rpm:	3000 RPM
locking device:Skwezloc Collarseries:SFTMH-Texpansion type:Non-Expansion Bearing (Fixed)replacement bearing:2-111radial dynamic load capacity:7901 lb	housing material:	Cast Iron
series: SFTMH-T expansion type: Non-Expansion Bearing (Fixed) replacement bearing: 2-111 radial dynamic load capacity: 7901 lb	lubrication type:	Lubrication Fitting
expansion type: Non-Expansion Bearing (Fixed) replacement bearing: 2-111 radial dynamic load capacity: 7901 lb	locking device:	Skwezloc Collar
replacement bearing: 2-111 radial dynamic load capacity: 7901 lb	series:	SFTMH-T
radial dynamic load capacity: 7901 lb	expansion type:	Non-Expansion Bearing (Fixed)
	replacement bearing:	2-111
manufacturer upc number: 662461340691	radial dynamic load capacity:	7901 lb
	manufacturer upc number:	662461340691