

# SNR 7036CVUJ74 angular contact ball bearings

Welcome to the SNR 7036CVUJ74 angular contact ball bearings 15 mm d online seller. 28 mm D

d	15 mm
D	28 mm
B	7 mm
a min	1.15 mm
a max	1.3 mm
Ca min	2 mm
Ca max	2.15 mm
rs min	0.3 mm
rNs min	0.3 mm
D3 max	26.7 mm
b min	0.95 mm
b max	1.2 mm
r0 max	0.25 mm
D4 max	30.8 mm
f	0.85 mm
Snap ring reference	R28
Radial clearance class	CN
Mass	0.02 kg
Dynamic load, C	3.65 kN
Static load, C0	2 kN
Fatigue limit load, Cu	0.09 kN
f0	14.8
Nlim (grease)	24,000 rpm

Min operating temperature, $T_{min}$	-20 °C
Max operating temperature, $T_{max}$	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.98 Hz
Characteristic outer ring frequency, BPF0	4.6 Hz
Characteristic inner ring frequency, BRFI	6.4 Hz
$d_a$ min	17 mm
$D_a$ max	26 mm
$r_a$ max	0.3 mm
$r_{Na}$ max	0.3 mm
$D_b$ min	31.5 mm