

SNR 7234BGM angular contact ball bearings

What are the types of SNR 7234BGM angular contact ball bearings ? Manufacturing Service . Get Your Free, 90 Outer Diameter (mm) Instant 130x90x60 Size (mm) price, design review.

Size (mm)	130x90x60
Bore Diameter (mm)	130
Outer Diameter (mm)	90
Width (mm)	60
d	90 mm
D	130 mm
B	60 mm
C	50 mm
α	5 °
dk	115 mm
b	9.5 mm
b1	9.5 mm
M	5 mm
r1 – min.	1 mm
r2 – min.	1 mm
da – min.	97.4 mm
da – max.	98.1 mm
Da – min.	112.9 mm
Da – max.	123.5 mm
ra – max.	1 mm
rb – max.	1 mm

Basic dynamic load rating – C	490 kN
Basic static load rating – C0	2450 kN
Specific factor dynamic load – K	100 N/mm2
Specific factor static load – K0	500 N/mm2
Constant – KM	330
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.75
EAN	7316576609497
Product Group	B04264
Self Aligning	Yes
Rolling Element	Spherical Plain
Material – Outer Member	Steel
Material – Ball	Steel
Material – Liner	Not Applicable
Relubricatable	Yes
Enclosure	2 Seals
Other Features	2 Piece Double Lip Seals Lubrication Hole and an Annular Groove in Both Rings
Long Description	90MM Bore; 50MM Housing Width; 130MM Outside Diameter; Spherical Plain; Steel Outer Member; Steel Ba
Inch – Metric	Metric
UNSPSC	31171515

Harmonized Tariff Code	8483.30.80.70
Noun	Bearing
Keyword 3	Spherical
Keyword String	Plain Spherical Radial
Manufacturer Item Number	GE 90 ES-2RS
Weight / LBS	6.063
Bore	3.543 Inch 90 Millimeter
Housing Width	1.969 Inch 50 Millimeter
Overall Width	2.362 Inch 60 Millimeter
Outside Diameter	5.118 Inch 130 Millimeter
bore diameter:	90 mm
inner ring material:	Chrome Steel
outside diameter:	130 mm
outer ring width:	50 mm
misalignment angle:	5 °
grade:	Commercial/Industrial
inner ring width:	60 mm
radial static load capacity:	2450 kN
bearing type:	Radial
radial dynamic load capacity:	490 kN
lubrication type:	Requires Lubrication
operating temperature range:	-30 to +130 °C °F
closure type:	Sealed
overall width:	60 mm
outer ring material:	Chrome Steel
manufacturer upc number:	7316576609497
Lubricant	Regular relubrication – grease

Design (sliding contact surface combination)	Steel/steel
Sealing solution	Double-lip seals
α	5 °
r1 min.	1 mm
r2 min.	1 mm
da min.	97.4 mm
da max.	98.1 mm
Da min.	112.9 mm
Da max.	123.5 mm
ra max.	1 mm
rb max.	1 mm
Basic dynamic load rating C	490 kN
Basic static load rating C0	2450 kN
Specific dynamic load factor K	100 N/mm ²
Specific static load factor K0	500 N/mm ²
Material constant KM	330
Mass plain bearing	2.75 kg