

SNR AB12437 deep groove ball bearings

Enjoy High Margins on Competitive 134.938 mm db Pricing.Great Wholesale Products at Low Costs. 120 mm da

da	120 mm
db	134.938 mm
dc	115.888 mm
Da	259.999 mm
Ca	95.809 mm
A1	158.75 mm
A2	279.4 mm
S	4.763 mm
ba	67.469 mm
H	320.675 mm
H1	160.325 mm
H2	63.5 mm
J min.	431.8 mm
J max.	463.55 mm
J1	95.25 mm
L	539.75 mm
N1	28.575 mm
R1	82.55 mm
R2	39.688 mm
RG	3/8 NPT
PG	1/4 NPT
h	60.325 mm
Housing	SAF 324

Bearing	22324 CC/W33
Lock nut	AN 24
Lock washer	W 24
Stabilizing ring	SR-0-24
Taconite seal (db shaft position)	TER 127
Taconite seal (dc shaft position)	TER 119
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	575 r/min
P60°	230 kN
P90°	138 kN
P120°	87.2 kN
P150°	80.1 kN
P180°	96.1 kN
Pa	62.3 kN
Mass pillow block	91.3 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	623.7 g