

# SNR FC35051 tapered roller bearings

SNR FC35051 tapered roller bearings Manufacturers , Online Wholesale Suppliers ! 65x100x18 Size (mm)

Size (mm)	65x100x18
Bore Diameter (mm)	65
Outer Diameter (mm)	100
Width (mm)	18
d	65 mm
D	100 mm
B	18 mm
C	18 mm
r min.	1.1 mm
da min.	71 mm
Da max.	94 mm
ra max.	1.0 mm
Weight	0.438 Kg
Basic dynamic load rating (C)	30,5 kN
Basic static load rating (C0)	25,2 kN
(Grease) Lubrication Speed	6500 r/min
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	65MM Bore; 100MM Outside Diameter; 18MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Fi
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	1.0048
Bore	2.559 Inch   65 Millimeter
Outer Race Width	0.709 Inch   18 Millimeter
Outside Diameter	3.937 Inch   100 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	65 mm
Width	18 mm
Fillet Radius/Chamfer	1.1 mm
Dynamic Load Rating	30,500 N
Static Load Rating	25,200 N
Limiting Speed – Grease	6,700 rpm
Limiting Speed – Oil	8,000 rpm

Factor fo	15.7
Radial Clearance	0.008 to 0.028 mm
da (min)	71 mm
Da (max)	94 mm
ra (max)	1 mm