

# SNR FC35079 tapered roller bearings

SNR FC35079 tapered roller bearings Deal is your source 101.6 mm da for OEM and accessories. We sell Genuine at discount prices.

da	101.6 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	155.575 mm
ba	46.831 mm
H	222.25 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	22.225 mm
R1	65.088 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	40.481 mm
Housing	SAFS 024 KA
Bearing	23024 CCK/W33
Adapter sleeve assembly	SNW 3024×4

Stabilizing ring	2 x 38151-24
Labyrinth ring	2 x LOR 657
PosiTrac Plus contact element	2 x B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac Plus seal	1350 r/min
P60°	175 kN
P90°	105 kN
P120°	64.9 kN
P150°	58.7 kN
P180°	71.2 kN
Pa	16.7 kN
Mass pillow block	39 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g