

# SNR ML7007HVDUJ74S angular contact ball bearings

High Quality SNR ML7007HVDUJ74S angular contact ball bearings. Competitive Pricing. Accept Small Order. Easy 40x52x7 Size (mm) 52 Outer Diameter (mm) and Fast Shipping.

Size (mm)	40x52x7
Bore Diameter (mm)	40
Outer Diameter (mm)	52
Width (mm)	7
d	40 mm
D	52 mm
B	7 mm
C	7 mm
a	1.3 mm
b	0.95 mm
f	0.85 mm
r min.	0.3 mm
r1 min.	0.3 mm
D1	50.7 mm
D2	54.8 mm
Weight	0.034 Kg
Basic dynamic load rating (C)	5,95 kN
Basic static load rating (C0)	4,9 kN
(Grease) Lubrication Speed	12000 r/min
Enclosure	Single Shield with Snap Ring
Bore Type	Cylindrical Bore
Configuration	Single Row

Bore Size	40 mm
Outside Diameter	52 mm
Width	7 mm
Fillet Radius/Chamfer	0.3 mm
r1	0.3 mm
Snap Ring Width	0.9 mm
Snap Ring Outside Diameter	54.8 mm
D1 (max)	50.7 mm
a (max)	1.3 mm
b (min)	1 mm
Dynamic Load Rating	5,950 N
Static Load Rating	4,900 N
Limiting Speed – Grease	12,000 rpm
Limiting Speed – Oil	14,000 rpm
Factor fo	16.2
Radial Clearance	0.006 to 0.020 mm
da (min)	42 mm
Da (max)	50 mm
Dx (min)	55.5 mm
ra (max)	0.3 mm
Cy (max)	1.8 mm