

# SNR R160.15 wheel bearings

How do 72 Outer Diameter (mm) I 30x72x19 Size (mm) place an EMERGENCY order for a SNR R160.15 wheel bearings that I want to pick up at a our store?

Size (mm)	30x72x19
Bore Diameter (mm)	30
Outer Diameter (mm)	72
Width (mm)	19
d	30 mm
D	72 mm
B	19 mm
C	19 mm
Angle ( $\alpha$ )	40 °
a	11.9 mm
r min.	1.1 mm
r1 min.	0.6 mm
2B	38 mm
da min.	35 mm
Da max.	67 mm
ra max.	0.6 mm
Weight	0.360 Kg
Basic dynamic load rating (C)	52 kN
Basic static load rating (C0)	42 kN
(Grease) Lubrication Speed	6100 r/min
Bore Type	Cylindrical Bore
Enclosure	Open
Configuration	Duplex

Bore Size	30 mm
Outside Diameter	72 mm
Width	19 mm
Fillet Radius/Chamfer	1.1 mm
r1	0.6 mm
Dynamic Load Rating	52,000 N
Static Load Rating	42,000 N
Limiting Speed – Grease	6,100 rpm
Limiting Speed – Oil	8,500 rpm
da1 (min)	37 mm
da2 (min)	35 mm
Da1 (max)	65 mm
Da2 (max)	67 mm
ra (max)	1 mm
ra1 (max)	0.6 mm