

SNR R170.07 wheel bearings

100% Authentic. N/A Minimum Buy Quantity SNR R170.07 wheel bearings TIMKEN Manufacturer Name Highest 0.0 Inventory Quality. Certified Supplier.

| | |
|---------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 274.17 |
| EAN | 0013992051172 |
| Product Group | B04144 |
| Number of Mounting Holes | 4 |
| Mounting Method | Clamp Collar |
| Housing Style | 4 Bolt Round Flange Block |
| Rolling Element | Cylindrical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Expansion |
| Mounting Bolts | 30 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | MSE800BX |
| Seals | Triple Lip Labyrinth |
| Housing Configuration | 2 Piece Split |
| Pilot Configuration | No Pilot |
| Inch – Metric | Inch |
| Long Description | 4 Bolt Round Flange Block; 8" Bore; 22-1/2" Bolt Circle; 2 Piece Split; Clamp Collar Mount |

| | |
|------------------------------------|--|
| Other Features | Single Row Wide Inner Ring Medium Duty |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Flanged |
| Weight / LBS | 603.9 |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| d | 8 Inch 203.2 Millimeter |
| Bolt Spacing | 15.9 Inch 404.5 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| Nominal Bolt Circle Diameter Round | 22.5 Inch 572 Millimeter |
| D | 6.142 Inch 156 Millimeter |
| Shaft Size | 8 in |
| Seal Type | Aluminium Triple Labyrinth |
| Bearing Type | Split Cylindrical Expansion Type |
| Support Type | Round Flange |
| Series Type | Medium Series |
| Bolt Size | 4 x M30 |
| Bearing – Housing – Seal | MSE800BXHATL |
| Bearing – Housing – Seal UPC | 013992044570 |
| Bearing UPC | 013992033178 |
| Dimension T | 25.5 in |
| Dimension R | 22.5 in |
| Dimension P | 1.3 in |
| Dimension H | 5.4 in |
| Dimension N | 19.375 in |
| Dimension V | 0.2 in |

| | |
|--------------------------|---|
| Dimension L | 10.1 in |
| Cr – Dynamic Load Rating | 227732 lbf |
| Cor – Static Load Rating | 340810 lbf |
| Maximum Speed | 960 rpm |
| Note | This product line was formerly known as “Revolvo” |