## SNR UC308G2 deep groove ball bearings

Online shopping SNR UC308G2 deep groove ball bearings from 0.0 Inventory TIMKEN Manufacturer Name N/A Minimum Buy Quantity a great selection at Store. ... Accessories.

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 4.99  |
| EAN                       | 0883450966160   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 12 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | 22209   |
| Seals                     | Triple Lip Viton  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch — Metric             | Metric  |
| Long Description          | 4 Bolt Square Flange Block;<br>40MM Bore; 140MM Bolt Circle;<br>98.8MM Bolt Spacing; 1 Piece<br>Solid; Concen |

| Other Features                        | Double Row   Single Collar  <br>With Set Screw |
|---------------------------------------|--|
| UNSPSC                                | 31171501                                       |
| Harmonized Tariff Code                | 8483.20.40.80                                  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Manufacturer Item Number              | QAFL09A040SEN                                  |
| Weight / LBS                          | 11   |
| d                                     | 1.575 Inch   40 Millimeter                     |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter                          |
| Nominal Bolt Circle Diameter<br>Round | 5.5 Inch   140 Millimeter                      |
| D                                     | 2.882 Inch   73.2 Millimeter                   |
| Bolt Spacing                          | 3.89 Inch   98.8 Millimeter                    |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter                          |