## SNR UC310-30 deep groove ball bearings

SNR UC310-30 deep groove ball bearings Manufacturers , Mounted Bearing Engineering Group Online Wholesale Suppliers[] ! 65 mm Shaft Size

| Engineering Group       | Mounted Bearing         |
|-------------------------|-------------------------|
| Shaft Size              | 65 mm                   |
| Shaft Size Type         | Metric                  |
| Full Timken Part Number | QMFL13J065SB            |
| Locking Style           | Eccentric               |
| Weight                  | 17.0 lb                 |
| Housing Style           | Four-Bolt Square Flange |
| UPC Code                | 0883450070324           |
| Dimension BC            | 6.75 in                 |
| Dimension C             | 3.62 in                 |
| Dimension D             | 5.750 in                |
| Dimension E             | 4.77 in                 |
| Dimension F             | 6.19 in                 |
| Dimension H             | 1.00 in                 |
| Dimension J (Bolt Size) | 0.625 in                |
| Dimension K             | 1.24 in                 |
| Dimension L Exp         | 3.57 in                 |
| Dimension L Fix         | 3.47 in                 |
| Dimension M             | 2.13 in                 |
| Dimension N             | 2.860 in                |
| Dimension R             | 0.12 in                 |
| Dimension S             | 2.32 in                 |

| C0 — Static Load                    | 48600 lb  |
|-------------------------------------|-----------|
| C — Dynamic Load (Basic)            | 46400 lb  |
| e — Geometry Factor                 | 0.25      |
| Y1 — Geometry Factor                | 2.69      |
| Y2 — Geometry Factor                | 4.00      |
| Oil Lubrication — M/N Seal          | 1800 rpm  |
| Oil Lubrication — T Seal            | 3200 rpm  |
| Oil Lubrication — B/C/O Seal        | 1500 rpm  |
| Grease Lubrication - M/N Seal       | 1800 rpm  |
| Grease Lubrication – T Seal         | 2800 rpm  |
| Grease Lubrication - B/C/O Seal     | 1500 rpm  |
| Float                               | 0.083 in  |
| Shaft Tolerance                     | 0.0015 in |
| Eng Internal Radial Clearance – Min | 0.0016    |
| Eng Internal Radial Clearance – Max | 0.0026    |
| Pre Install Clearance Min           | 0.0016 in |
| Pre Install Clearance Max           | 0.0026 in |
|                                     |           |