

SNR UCFCE210 bearing units

SNR UCFCE210 bearing units Deal is your 40×3.5×10 Size (mm) source for OEM 3,5 Outer Diameter (mm) and accessories. We sell Genuine at discount prices. 40 Bore Diameter (mm)

| | |
|---------------------------------------|---------------|
| Size (mm) | 40×3.5×10 |
| Bore Diameter (mm) | 40 |
| Outer Diameter (mm) | 3,5 |
| Width (mm) | 10 |
| d | 40 mm |
| A1 | 3.5 mm |
| A2 | 10 mm |
| B | 49.2 mm |
| B4 | 8 mm |
| Da – min. | 87 mm |
| J | 119 mm |
| H | 13.5 mm |
| s1 | 30.2 mm |
| T | 33.7 mm |
| Basic dynamic load rating – C | 30.7 kN |
| Basic static load rating – C0 | 19 kN |
| Fatigue load limit – Pu | 0.8 kN |
| Permissible radial housing load | max. 7.5 kN |
| Weight | 1.25 kg |
| Thread – G2 | M8x1 |
| Hexagonal key size for grub screw – H | 4 mm |
| Housing material | Pressed steel |
| Da min. | 87 mm |

| | |
|---|-------------|
| N | 13.5 mm |
| Basic dynamic load rating C | 30.7 kN |
| Basic static load rating C0 | 19 kN |
| Fatigue load limit Pu | 0.8 kN |
| Permissible radial housing load max. | 7.5 kN |
| Mass unit | 1.25 kg |
| Thread grub screw G2 | M8x1 |
| Hexagonal key size for grub screw N | 4 mm |
| Recommended tightening torque for grub screw | 6.5 N·m |
| Recommended diameter for attachment bolts, mm G | 12 mm |
| Recommended diameter for attachment bolts, inch G | 0.5 in |
| Bearing | YAR 208-2RF |
| Housing | PF 80 |