

SNR UCFCE210 bearing units

SNR UCFCE210 bearing units Deal is your 40×3.5×10 Size (mm) source for OEM 3,5 Outer Diameter (mm) and accessories. We sell Genuine at discount prices. 40 Bore Diameter (mm)

Size (mm)	40×3.5×10
Bore Diameter (mm)	40
Outer Diameter (mm)	3,5
Width (mm)	10
d	40 mm
A1	3.5 mm
A2	10 mm
B	49.2 mm
B4	8 mm
Da – min.	87 mm
J	119 mm
H	13.5 mm
s1	30.2 mm
T	33.7 mm
Basic dynamic load rating – C	30.7 kN
Basic static load rating – C0	19 kN
Fatigue load limit – Pu	0.8 kN
Permissible radial housing load	max. 7.5 kN
Weight	1.25 kg
Thread – G2	M8x1
Hexagonal key size for grub screw – H	4 mm
Housing material	Pressed steel
Da min.	87 mm

N	13.5 mm
Basic dynamic load rating C	30.7 kN
Basic static load rating C0	19 kN
Fatigue load limit Pu	0.8 kN
Permissible radial housing load max.	7.5 kN
Mass unit	1.25 kg
Thread grub screw G2	M8x1
Hexagonal key size for grub screw N	4 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	12 mm
Recommended diameter for attachment bolts, inch G	0.5 in
Bearing	YAR 208-2RF
Housing	PF 80