

SNR UCPL211 bearing units

SNR UCPL211 bearing units Needs Analysis , 73.025 mm da
Manufacturing Service . Get Your Free.

da	73.025 mm
Da	150 mm
Ca	45.796 mm
A1	88.9 mm
A2	195.262 mm
S	4.763 mm
ba	35.719 mm
H	187.325 mm
H1	95.25 mm
H2	38.1 mm
J min.	250.825 mm
J max.	279.4 mm
L	330.2 mm
N1	23.813 mm
R1	53.975 mm
R2	22.225 mm
RG	3/8 NPT
PG	1/8 NPT
h	34.925 mm
Housing	SAFS 517
Bearing	22217 EK
Adapter sleeve assembly	SNW 17×2.7/8
Stabilizing ring	SR-17-14
Taconite seal	TER 52

End plug (suffix Y)	EPR 9
Max. speed for Taconite seal	1050 r/min
P60°	78.7 kN
P90°	47.2 kN
P120°	28.9 kN
P150°	26.7 kN
P180°	32 kN
Pa	9.25 kN
Mass pillow block	24.5 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	110.56 g