

SNR UK216+H-43 deep groove ball bearings

SNR UK216+H-43 deep groove ball bearings Product Brochures 30x72x23.8 Size (mm) , 72 Outer Diameter (mm) Manufacturing Service . Get Your Free.

Size (mm)	30x72x23.8
Bore Diameter (mm)	30
Outer Diameter (mm)	72
Width (mm)	23,8
D	72 mm
d	30 mm
B	23.8 mm
d1	38.7 mm
D1	55.2 mm
r1,2 – min.	1 mm
a	36 mm
Basic dynamic load rating – C	25.1 kN
Basic static load rating – C0	16.3 kN
Fatigue load limit – Pu	0.695 kN
Maximum dynamic radial loads – Fr	max. 17 kN
Maximum static radial loads – F0r	max. 24 kN
Limiting speed	5000 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.499
EAN	7316577008114

Product Group	B00152
roller diameter:	72 mm
radial static load capacity:	5510 lbf
roller width:	23.8 mm
roller material:	Chrome Steel
bore diameter:	30 mm
maximum rpm:	5000 RPM
roller shape:	Flat
lubrication hole location:	Inner Ring
bearing element:	Balls – Two Rows
axial dynamic load capacity:	6070 lbf
closure type:	Shielded
axial static load capacity:	3820 lbf
operating temperature range:	Maximum of +300 °F
finish/coating:	Uncoated
radial dynamic load capacity:	3890 lbf
standards met:	ANSI/ABMA Standard 18.1
d1 ≈	38.7 mm
D1 ≈	55.2 mm
r1,2 min.	1 mm
Basic dynamic load rating C	25.1 kN
Basic static load rating C0	16.3 kN
Fatigue load limit Pu	0.695 kN
Maximum dynamic radial load Fr max.	17 kN
Maximum static radial load F0r max.	24 kN
Mass cam roller	0.49 kg