

# T7FC060 NSK 60x125x37mm Basic static load rating (C0) 197 kN Tapered roller bearings

Bearing code	T7FC060
SKF code	60125/37
Group	60
Basic dynamic rating (C)	197
Basic static rating (C0)	197
ISO 15024 code	04
d	60 mm
D	125 mm
T	37 mm
B	71.5 mm
C	26 mm
r	61.5 mm
r1 min.	2 mm
r1 max.	3 mm
DB min.	78 mm
DB max.	88 mm
DB1 min.	112 mm
DB1 max.	72 mm
DB2 min.	119 mm
DB2 max.	23.5 mm
DB3 min.	23.5 mm
W	2.85 kg
Basic dynamic load rating (C)	197 kN
Basic static load rating (C0)	197 kN
ISO standard	2800 r/min
ISO 15024	2800 r/min
Factor (a1)	0.82
Factor (a2)	0.4
Factor (a3)	1
Factor (a4)	1
Factor (a5)	1
Factor (a6)	1
Factor (a7)	1
Factor (a8)	1
Factor (a9)	1
Factor (a10)	1
Factor (a11)	1
Factor (a12)	1
Factor (a13)	1
Factor (a14)	1
Factor (a15)	1
Factor (a16)	1
Factor (a17)	1
Factor (a18)	1
Factor (a19)	1
Factor (a20)	1
Factor (a21)	1
Factor (a22)	1
Factor (a23)	1
Factor (a24)	1
Factor (a25)	1
Factor (a26)	1
Factor (a27)	1
Factor (a28)	1
Factor (a29)	1
Factor (a30)	1
Factor (a31)	1
Factor (a32)	1
Factor (a33)	1
Factor (a34)	1
Factor (a35)	1
Factor (a36)	1
Factor (a37)	1
Factor (a38)	1
Factor (a39)	1
Factor (a40)	1
Factor (a41)	1
Factor (a42)	1
Factor (a43)	1
Factor (a44)	1
Factor (a45)	1
Factor (a46)	1
Factor (a47)	1
Factor (a48)	1
Factor (a49)	1
Factor (a50)	1
Factor (a51)	1
Factor (a52)	1
Factor (a53)	1
Factor (a54)	1
Factor (a55)	1
Factor (a56)	1
Factor (a57)	1
Factor (a58)	1
Factor (a59)	1
Factor (a60)	1
Factor (a61)	1
Factor (a62)	1
Factor (a63)	1
Factor (a64)	1
Factor (a65)	1
Factor (a66)	1
Factor (a67)	1
Factor (a68)	1
Factor (a69)	1
Factor (a70)	1
Factor (a71)	1
Factor (a72)	1
Factor (a73)	1
Factor (a74)	1
Factor (a75)	1
Factor (a76)	1
Factor (a77)	1
Factor (a78)	1
Factor (a79)	1
Factor (a80)	1
Factor (a81)	1
Factor (a82)	1
Factor (a83)	1
Factor (a84)	1
Factor (a85)	1
Factor (a86)	1
Factor (a87)	1
Factor (a88)	1
Factor (a89)	1
Factor (a90)	1
Factor (a91)	1
Factor (a92)	1
Factor (a93)	1
Factor (a94)	1
Factor (a95)	1
Factor (a96)	1
Factor (a97)	1
Factor (a98)	1
Factor (a99)	1
Factor (a100)	1