

Timken 100RJ02 cylindrical roller bearings

Shop 380 Outer Diameter (mm) Timken 100RJ02 cylindrical roller bearings huge online discount inventory. and Import 600 Bore Diameter (mm) machinery parts your 600x380x210 Size (mm) car needs with Free Shipping and Free Extended Warranty.

| | |
|---------------------|-------------|
| Size (mm) | 600x380x210 |
| Bore Diameter (mm) | 600 |
| Outer Diameter (mm) | 380 |
| Width (mm) | 210 |
| d1 | 380 mm |
| D | 600 mm |
| B1 | 210 mm |
| d2 | 457 mm |
| d3 | 470 mm |
| D1 | 554 mm |
| B | 148 mm |
| B2 | 52 mm |
| B5 | 66 mm |
| s1 | 30.6 mm |
| r1,2 – min. | 5 mm |
| da – max. | 486 mm |
| db – min. | 417 mm |
| Da – min. | 523 mm |
| Da – max. | 582 mm |
| Ba – min. | 15 mm |
| Ca – min. | 2.1 mm |

| | |
|-------------------------------|------------|
| ra – max. | 4 mm |
| Basic dynamic load rating – C | 3650 kN |
| Basic static load rating – C0 | 6200 kN |
| Fatigue load limit – Pu | 450 kN |
| Reference speed | 800 r/min |
| Limiting speed | 1100 r/min |
| Factor – k1 | 0.121 |
| Factor – k2 | 0.099 |
| d2 ≈ | 457 mm |
| D1 ≈ | 554 mm |
| s1 max. | 30.6 mm |
| r1,2 min. | 5 mm |
| da max. | 486 mm |
| db min. | 417 mm |
| Da min. | 523 mm |
| Da max. | 582 mm |
| Ba min. | 15 mm |
| Ca min. | 2.1 mm |
| ra max. | 4 mm |
| Basic dynamic load rating C | 3650 kN |
| Basic static load rating C0 | 6200 kN |
| Fatigue load limit Pu | 450 kN |
| Misalignment factor k1 | 0.121 |
| Operating clearance factor k2 | 0.099 |
| Mass bearing + sleeve | 175 kg |