

Timken 1015KRRB deep groove ball bearings

Timken 1015KRRB deep groove ball bearings Deal is your source for OEM and accessories. 50x90x20 Size (mm) We sell Genuine at 90,000 Outer Diameter (mm) discount prices.

Size (mm)	50x90x20
Bore Diameter (mm)	50,000
Outer Diameter (mm)	90,000
Width (mm)	20,000
d	50,000 mm
D	90,000 mm
B	20,000 mm
C	20,000 mm
rs min	1.1 mm
Radial clearance class	CN
Mass	0.45 kg
Dynamic load, C	35 kN
Static load, C0	23.2 kN
Fatigue limit load, Cu	1.05 kN
f0	14.4
Nlim (grease)	4,700 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.33 Hz

Characteristic outer ring frequency, BPF0	4.09 Hz
Characteristic inner ring frequency, BPI	5.91 Hz
da min	56.5 mm
da max	60 mm
Da max	83.5 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.442
EAN	4547359366006
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	50MM Bore; 90MM Outside Diameter; 20MM Outer Race Width; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No F

Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6210LU
Weight / LBS	0.974
Outside Diameter	3.543 Inch 90 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.969 Inch 50 Millimeter
bore diameter:	50 mm
precision rating:	ISO Class 0
outside diameter:	90 mm
finish/coating:	Uncoated
overall width:	20 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Single Seal
inner ring width:	20 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	20 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	4700 rpm
internal clearance:	CN
fillet radius:	1.1 mm

operating temperature range:	-40 to 120 °C
maximum rpm:	8300 RPM
dynamic load capacity:	35000 N
series:	62
static load capacity:	23200 N
manufacturer product page:	Click here