

# Timken 16582/16522 tapered roller bearings

Enjoy High Margins on 28.575×41.275×25.4 Size (mm) Competitive Pricing.Great Wholesale Products at Low Costs. 41,275 Outer Diameter (mm)

Size (mm)	28.575×41.275×25.4
Bore Diameter (mm)	28,575
Outer Diameter (mm)	41,275
Width (mm)	25,4
Fw	28,575 mm
D	41,275 mm
C	25,4 mm
r5 min.	1,02 mm
Weight	0,104 Kg
Basic dynamic load rating (C)	36,3 kN
Basic static load rating (C0)	53,8 kN
(Grease) Lubrication Speed	16000 r/min
Inventory	15.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.1
EAN	0605790195150
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly with Outer Ring – No Inner Ring
Enclosure	Open

Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	No
Inch – Metric	Inch
Relubricatable	Yes
Thrust Bearing	No
Long Description	1-1/8" Bore; 1-5/8" Outside Diameter; 1" Width; Needle Roller Bearing; Roller Assembl
Other Features	2 Rib Outer Ring   Steel Cage   Heavy Duty   Oil Hole
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer Item Number	HJ-182616
Weight / LBS	0.23
Width	1 Inch   25.4 Millimeter
Outside Diameter	1.625 Inch   41.275 Millimeter
Bore	1.125 Inch   28.575 Millimeter
Bearing No.	HJ-182616
rs(min)	1.02
Used with inner ring No.	IR-141816
Cr	25.4
C0r	53.8

Cu	8.45
Grease lub.	10000
Oil lub.	16000
(Refer.)Mass(kg)	0.104
Clearance fit S(h6)(max.)	28.575
Clearance fit S(h6)(min.)	28.562
Clearance fit H(H7)(max.)	41.300
Clearance fit H(H7)(min.)	41.275
Tight transition fit S(f6)(max.)	28.555
Tight transition fit S(f6)(min.)	28.542
Tight transition fit H(N7)(max.)	41.267
Tight transition fit H(N7)(min.)	41.242
Da	36.53