

Timken 19138X/19283 tapered roller bearings

170 Million used Timken 19138X/19283 tapered roller bearings instantly searchable. Shop our 40 Bore Diameter (mm) large selection of parts based on brand, 75 Outer Diameter (mm) price, 40x75x26 Size (mm) description, and location. Order the with stock ...

Size (mm)	40x75x26
Bore Diameter (mm)	40
Outer Diameter (mm)	75
Width (mm)	26
d	40 mm
D	75 mm
T	26 mm
B	26 mm
C	20,5 mm
a	18,3 mm
r min.	1,5 mm
r2 min.	1,5 mm
da min.	48,5 mm
da max	47 mm
Da min	65 mm
Da max.	66,5 mm
Db min.	71 mm
ra max.	1,5 mm
rb max.	1,5 mm
Weight	0,508 Kg

Basic dynamic load rating (C)	82,2 kN
Basic static load rating (C0)	108 kN
(Grease) Lubrication Speed	5200 r/min
(Oil) Lubrication Speed	6900 r/min
Calculation factor (e)	0,36
Calculation factor (Y0)	0,93
Bearing No.	33108JR
r(min)	1.5
r1(min)	1.5
Cr	103
C0r	108
Cu	16.1
Grease lub.	5200
Oil lub.	6900
a(mm)	18.3
da(min)	48.5
db(max)	47
Da(max)	66.5
Da(min)	65
Db(min)	71
Sa(min)	4
Sb(min)	5.5
ra(max)	1.5
rb(max)	1.5
e	0.36
Y1	1.69
Y0	0.93
(Refer.) Mass (kg)	0.508