

# Timken 232/530YMB spherical roller bearings

Request A Quote For Your Special Timken 232/530YMB spherical roller bearings 0.0 Inventory Needs Today! Free Quotes. ISO 9001 certified. TIMKEN Manufacturer Name N/A Minimum Buy Quantity

|                           |                          |
|---------------------------|--------------------------|
| Inventory                 | 0.0                      |
| Manufacturer Name         | TIMKEN                   |
| Minimum Buy Quantity      | N/A                      |
| Weight                    | 4.086                    |
| EAN                       | 0883450294331            |
| Product Group             | M06288                   |
| Number of Mounting Holes  | 2                        |
| Mounting Method           | Eccentric Collar         |
| Housing Style             | 2 Bolt Pillow Block      |
| Rolling Element           | Spherical Roller Bearing |
| Housing Material          | Cast Steel               |
| Expansion / Non-expansion | Expansion                |
| Mounting Bolts            | 5/8 Inch                 |
| Relubricatable            | Yes                      |
| Insert Part Number        | 22209                    |
| Seals                     | Double Lip Viton         |
| Housing Configuration     | 1 Piece Solid            |
| Inch – Metric             | Metric                   |
| Other Features            | Double Row               |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 40MM Bore; 57.2MM Base to Center Height; Eccentric Collar Mount; Spherical Roll |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QMP09J040SEC   |
| Weight / LBS                  | 10   |
| d                             | 1.575 Inch   40 Millimeter   |
| Nominal Bolt Center to Center | 6.7 Inch   170 Millimeter  |
| B                             | 2.252 Inch   57.2 Millimeter   |
| D                             | 2.875 Inch   73.02 Millimeter  |
| Bolt Spacing Maximum          | 7.12 Inch   180.848Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Bolt Spacing Minimum          | 6.25 Inch   158.75Millimeter   |