

# Timken 25583/25519 tapered roller bearings

Timken 25583/25519 tapered roller bearings Deal is your source for OEM and 38,1 mm d accessories. We sell Genuine at discount 38,1 Bore Diameter (mm) prices.

|                               |          |
|-------------------------------|----------|
| Bore Diameter (mm)            | 38,1     |
| d                             | 38,1 mm  |
| s1                            | 30,2 mm  |
| A                             | 47,6 mm  |
| A1                            | 32 mm    |
| B                             | 49,2 mm  |
| G                             | 12 mm    |
| H                             | 108 mm   |
| H1                            | 54 mm    |
| H2                            | 20,6 mm  |
| J                             | 143,7 mm |
| L                             | 187,5 mm |
| N                             | 22,7 mm  |
| N1                            | 14 mm    |
| Weight                        | 2,55 Kg  |
| Basic dynamic load rating (C) | 33,2 kN  |
| Basic static load rating (C0) | 21,6 kN  |
| Fatigue load limit (Pu)       | 0,915    |
| Inventory                     | 0.0      |
| Manufacturer Name             | SKF      |
| Minimum Buy Quantity          | N/A      |
| Weight / Kilogram             | 2.5      |

|                           |                                                                                            |
|---------------------------|--------------------------------------------------------------------------------------------|
| EAN                       | 7316577755889                                                                              |
| Product Group             | M06110                                                                                     |
| Number of Mounting Holes  | 2                                                                                          |
| Mounting Method           | Set Screw                                                                                  |
| Housing Style             | 2 Bolt Pillow Block                                                                        |
| Rolling Element           | Ball Bearing                                                                               |
| Housing Material          | Cast Iron                                                                                  |
| Expansion / Non-expansion | Non-expansion                                                                              |
| Mounting Bolts            | 1/2 Inch                                                                                   |
| Relubricatable            | Yes                                                                                        |
| Insert Part Number        | YAR 209-108-2F                                                                             |
| Seals                     | M Seal                                                                                     |
| Housing Configuration     | 1 Piece Solid                                                                              |
| Inch – Metric             | Inch                                                                                       |
| Other Features            | Single Row   Medium Duty   Wide Inner Race   Has Flinger                                   |
| Long Description          | 2 Bolt Pillow Block; 1-1/2" Bore; 2-1/8" Base to Center Height; Set Screw Mount; Ball Bear |
| UNSPSC                    | 31171511                                                                                   |
| Harmonized Tariff Code    | 8483.20.40.40                                                                              |
| Noun                      | Bearing                                                                                    |
| Keyword String            | Pillow Block                                                                               |
| Manufacturer Item Number  | SYM 1.1/2 TF                                                                               |
| Weight / LBS              | 5.5                                                                                        |
| Bore                      | 1.5 Inch   38.1 Millimeter                                                                 |
| Length Thru Bore          | 1.938 Inch   49.225 Millimeter                                                             |
| Bolt Spacing Maximum      | 6 Inch   152.4Millimeter                                                                   |
| Bolt Spacing Minimum      | 5.313 Inch   134.95Millimeter                                                              |

|                               |                               |
|-------------------------------|-------------------------------|
| Actual Bolt Center to Center  | 0 Inch   0Millimeter          |
| Base to Center Height         | 2.125 Inch   53.98 Millimeter |
| Nominal Bolt Center to Center | 5.9 Inch   150 Millimeter     |