

Timken 2578/2524YD tapered roller bearings

How do I place an EMERGENCY order for a Timken 2578/2524YD tapered roller bearings that I want to 190 Outer Diameter (mm) pick up at a our 240x190x24 Size (mm) store?

Size (mm)	240x190x24
Bore Diameter (mm)	240
Outer Diameter (mm)	190
Width (mm)	24
d	190 mm
D	240 mm
B	24 mm
d1	206 mm
D1	224 mm
r1,2 – min.	1.5 mm
da – min.	197 mm
Da – max.	233 mm
ra – max.	1.5 mm
Basic dynamic load rating – C	76.1 kN
Basic static load rating – C0	98 kN
Fatigue load limit – Pu	2.8 kN
Reference speed	5300 r/min
Limiting speed	3200 r/min
Calculation factor – kr	0.015
Calculation factor – f0	17.1
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	190MM Bore; 240MM Outside Diameter; 24MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No F
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	2.25
Outer Race Width	0.945 Inch 24 Millimeter
Bore	7.48 Inch 190 Millimeter
Outside Diameter	9.449 Inch 240 Millimeter
Inner Race Width	0 Inch 0 Millimeter
d1 ≈	206 mm
D1 ≈	224 mm
r1,2 min.	1.5 mm
da min.	197 mm

Da max.	233 mm
ra max.	1.5 mm
Basic dynamic load rating C	76.1 kN
Basic static load rating C0	98 kN
Fatigue load limit Pu	2.8 kN
Calculation factor kr	0.015
Calculation factor f0	17.1
Mass bearing	2.24 kg