## Timken 2580A/2520A tapered roller bearings

Timken 2580A/2520A tapered roller bearings Warehouse offers car parts and car accessories. We sell discount 0.0 Inventory online as well as cheap machinery parts. ASAHI BEARINGS Manufacturer Name

| Inventory                 | 0.0                                                                                         |
|---------------------------|---------------------------------------------------------------------------------------------|
| Manufacturer Name         | ASAHI BEARINGS                                                                              |
| Minimum Buy Quantity      | N/A                                                                                         |
| Weight                    | 3.2                                                                                         |
| EAN                       | 0808250324262                                                                               |
| Product Group             | M06110                                                                                      |
| Number of Mounting Holes  | 2                                                                                           |
| Mounting Method           | Set Screw                                                                                   |
| Housing Style             | 2 Bolt Flange Block                                                                         |
| Rolling Element           | Ball Bearing                                                                                |
| Housing Material          | Nickel Coated Cast Iron                                                                     |
| Expansion / Non-expansion | Non-expansion                                                                               |
| Mounting Bolts            | 5/8 Inch                                                                                    |
| Relubricatable            | Yes                                                                                         |
| Insert Part Number        | UC211-32                                                                                    |
| Seals                     | Contact Seal                                                                                |
| Housing Configuration     | 1 Piece Solid                                                                               |
| Pilot Configuration       | No Pilot                                                                                    |
| Inch — Metric             | Inch                                                                                        |
| Long Description          | 2 Bolt Flange Block; 2" Bore;<br>7.3" Bolt Circle; 7-1/4" Bolt<br>Spacing; 1 Piece Solid; S |

| Other Features                        | Single Row   Spherical  <br>Normal Duty   Has Slinger |
|---------------------------------------|-------------------------------------------------------|
| UNSPSC                                | 31171501                                              |
| Harmonized Tariff Code                | 8483.20.40.40                                         |
| Noun                                  | Bearing                                               |
| Keyword String                        | Flanged                                               |
| Weight / LBS                          | 7.05                                                  |
| D                                     | 2.189 Inch   55.6 Millimeter                          |
| Bolt Spacing                          | 7.25 Inch   184.15 Millimeter                         |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter                                 |
| d                                     | 2 Inch   50.8 Millimeter                              |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter                                 |
| Nominal Bolt Circle Diameter<br>Round | 7.3 Inch   184.2 Millimeter                           |