

Timken 2788A/2736 tapered roller bearings

Timken 2788A/2736 tapered roller bearings 0.0 Inventory Product Brochures , Manufacturing Service . Get Your Free.

| | |
|---------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight | 58.5 |
| EAN | 0029176027338 |
| Product Group | B04311 |
| Internal Clearance | C0-Medium |
| Mounting Method | Shaft Mount |
| Rolling Element | Spherical Roller Bearing |
| Bore Profile | Straight |
| Cage Material | Bronze |
| Enclosure | Open |
| Number of Rows of Rollers | Double Row |
| Relubricatable | Yes |
| Withdrawal Sleeve | Not Applicable |
| Inch – Metric | Metric |
| Long Description | 170MM Straight Bore; 360MM Outside Diameter; 120MM Width; C0-Medium Clearance; Shaft Mount; Double R |
| UNSPSC | 31171510 |
| Harmonized Tariff Code | 84823080 |
| Noun | Bearing |
| Keyword String | Spherical |

| | |
|--------------------------|---|
| Manufacturer Item Number | 22334CAME4 |
| Weight / LBS | 58.5 |
| D | 14.173 Inch 360 Millimeter |
| B | 4.724 Inch 120 Millimeter |
| d | 170 |
| Adapter Part Number | Not Applicable Inch Not Applicable Millimeter |
| Y3 | 1.9 |
| hidYobi | 22334CAME4 |
| LangID | 1 |
| Y1 | 1.9 |
| D_ | 360 |
| Y2 | 2.9 |
| Macha rpm | 2000 |
| C | 1970 |
| B_ | 120 |
| da min | 188 |
| hidTable | ecat_NSSPHR |
| Oil rpm | 1200 |
| da max | 0 |
| Y0 | 1.9 |
| mass | 57.9 |
| GRS rpm | 1000 |
| ra | 3 |
| TSR rpm | 1300 |
| C0 | 2110 |
| DE_ | 316.67 |
| X0 | 1 |
| Prod_Type3 | SRB_CTB_CB |

| | |
|---------|------------|
| X1 | 1 |
| X2 | 0.67 |
| SIR | 44.49 |
| e | 0.35 |
| DA_ | 52 |
| bomp | 22334CAME4 |
| Z_ | 14 |
| ALP2 | 0 |
| ALP1 | 13 |
| ALP3 | 0 |
| D_a max | 342 |
| D_a min | 304 |
| yobi | 22334CAME4 |
| HPS | HPS |
| ALPHA_ | 0.227 |
| SDM_ | 266.003 |
| r | 4 |
| SBRG | 23 |
| DI_ | 215.336 |