

# Timken 31593/31520-B tapered roller bearings

With over 10170 full-service stores, our Timken 31593/31520-B tapered roller bearings inventory is extensive and 0.0 Inventory our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	174 lb
EAN	0013992056405
Product Group	B04144
Number of Mounting Holes	4
Mounting Method	Clamp Collar
Housing Style	4 Bolt Pillow Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	24 Millimeter
Relubricatable	Yes
Insert Part Number	LSE412BX
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Single Row   Light Duty   With Support   Wide Inner Ring
UNSPSC	31171511

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Weight / LBS	161.72
Actual Bolt Center to Center	17.7 Inch   450Millimeter
d	4.75 Inch   120.65 Millimeter
Nominal Bolt Center to Center	17.7 Inch   450 Millimeter
B	6.378 Inch   162 Millimeter
D	3.74 Inch   95 Millimeter
Bolt Spacing Minimum	0 Inch   0Millimeter
Bolt Spacing Maximum	0 Inch   0Millimeter
Shaft Size	4.75 in
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Expansion Type
Support Type	Four-Bolt Plummer Block
Series Type	Light Series
Pillow/Plummer Block Style	Split Cylindrical Housed Unit – Standard
Bolt Size	4 x M24
Dimension H	6.378 in
Dimension H1	1.5 in
Dimension H2	14.6 in
Dimension J	17.7 in
Dimension K	4.7 in
Dimension L	20.0 in
Dimension M	7.0 in
Housing Width	6.1 in
Cr – Dynamic Load Rating	81606 lbf

Cor – Static Load Rating	111505 lbf
Maximum Speed	1740 rpm
Note	This product line was formerly known as “Revolvo”