

# Timken 33262/33462D+X1S-33262 tapered roller bearings

Welcome to the 0.0 Inventory Timken 33262/33462D+X1S-33262 tapered roller bearings online seller.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 2.951  |
| EAN                       | 0662327985233  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Tapered Adapter Sleeve   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | B22623HL   |
| Seals                     | Floating Labyrinth   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Extended Inner Race   |
| Long Description          | 2 Bolt Pillow Block; 1-7/16" Bore; 1-7/8" Base to Center Height; Tapered Adapter Sleeve Mo |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | PB22623H                       |
| Manufacturer Internal Number  | 5898523                        |
| Weight / LBS                  | 7                              |
| B                             | 1.875 Inch   47.63 Millimeter  |
| d                             | 1.438 Inch   36.525 Millimeter |
| D                             | 2.71 Inch   68.834 Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter           |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter           |
| Nominal Bolt Center to Center | 5.3 Inch   133.5 Millimeter    |
| Actual Bolt Center to Center  | 5 Inch   127Millimeter         |