

Timken 3583/3525-B tapered roller bearings

offers a Timken 3583/3525-B tapered roller bearings selection of Genuine at Wholesale Prices. We are a Timken 3583/3525-B tapered roller bearings Certified Parts 70x150x54 Size (mm) Retailer

Size (mm)	70x150x54
Bore Diameter (mm)	70
Outer Diameter (mm)	150
Width (mm)	54
d	70 mm
D	150 mm
T	54 mm
B	51 mm
C	42 mm
a	36 mm
r min.	3 mm
r1 min.	2,5 mm
da min.	91 mm
Da min	124 mm
Da max.	138 mm
db max.	86 mm
Db min.	140 mm
ra max.	2,5 mm
rb max.	2 mm
Weight	4,35 Kg
Basic dynamic load rating (C)	300 kN

Basic static load rating (C0)	390 kN
(Grease) Lubrication Speed	2600 r/min
(Oil) Lubrication Speed	3400 r/min
Calculation factor (e)	0,35
Calculation factor (Y0)	0,96
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B04334
LangID	1
outer r	2.5
D_	150
TC-BET22	0
TC-BET21	4
TC-BET23	0
inner r	3
mass	4.35
GRS rpm	2600
D_b	140
Cr	30500
TC-RA	306.794
DE_	129.384
T-ALP23	20
db	86
T-ALP22	54
Prod_Type3	TRBSR_MD_A
da	91
T-ALP21	25

Iso	2GD
ALPHA_	12.953
SDM_	109.619
SBRG	23
D_a2	124
hidYobi	HR32314J
Y1	1.7
D_a1	138
B_	51
hidTable	ecat_NSTPRM
Oil rpm	3400
C0r	39500
Y0	0.96
TC-SLR	36
inner ra	2.5
outer rb	2
C0	390
Sa	4
Sb	12
e	0.35
DA_	20.163
Z_	16
C_	42
yobi	HR32314J
TC-DA1	21.412
TC-DA2	18.913
KBRG	3111
DI_	89.853