

Timken

36690/36620DC+X1S-36690

tapered roller bearings

Browse Timken 36690/36620DC+X1S-36690 tapered roller bearings Categories 35 Outer Diameter (mm) in the Manufacturers Online Free. 15x35x11 Size (mm) including .

Size (mm)	15x35x11
Bore Diameter (mm)	15
Outer Diameter (mm)	35
Width (mm)	11
d	15 mm
D	35 mm
B	11 mm
C	11 mm
ra1 max.	0,3 mm
Angle (α)	40 °
a	16 mm
r min.	0,6 mm
r1 min.	0,3 mm
2B	22 mm
da min.	19,5 mm
ra max.	0,6 mm
Db max	32,5 mm
Weight	0,092 Kg
Basic dynamic load rating (C)	13,6 kN
Basic static load rating (C0)	8,7 kN

(Grease) Lubrication Speed	15 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.091
EAN	4547359436686
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	2 (1 Pair)
Mounting Arrangement	Duplex-Back to Back
Inch – Metric	Metric
Long Description	15MM Bore; 35MM Outside Diameter; 22MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Ba
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7202BDB
Weight / LBS	0.2

Bore	0.591 Inch 15 Millimeter
Width	0.866 Inch 22 Millimeter
Outside Diameter	1.378 Inch 35 Millimeter