

Timken 387AS/384ED+X1S-387 tapered roller bearings

offers a Timken 387AS/384ED+X1S-387 tapered roller bearings selection 60 Outer Diameter (mm) of 95x60x18 Size (mm) Genuine at Wholesale Prices. We are a Timken 387AS/384ED+X1S-387 tapered roller bearings Certified 95 Bore Diameter (mm) Parts Retailer

Size (mm)	95x60x18
Bore Diameter (mm)	95
Outer Diameter (mm)	60
Width (mm)	18
d	60 mm
D	95 mm
B	18 mm
d1	71.3 mm
D2	86.5 mm
r1,2 – min.	1.1 mm
da – min.	66 mm
da – max.	71.2 mm
Da – max.	89 mm
ra – max.	1 mm
Basic dynamic load rating – C	30.7 kN
Basic static load rating – C0	23.2 kN
Fatigue load limit – Pu	0.98 kN
Reference speed	15000 r/min
Limiting speed	7500 r/min
Calculation factor – kr	0.025

Calculation factor – f0	15.6
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.442
EAN	7316573400523
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	60MM Bore; 95MM Outside Diameter; 18MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6012-2Z
Weight / LBS	0.97
Bore	2.362 Inch 60 Millimeter
Outside Diameter	3.74 Inch 95 Millimeter
Outer Race Width	0.709 Inch 18 Millimeter
d1 ≈	71.3 mm

D2 ≈	86.5 mm
r _{1,2} min.	1.1 mm
d _a min.	66 mm
d _a max.	71.2 mm
D _a max.	89 mm
r _a max.	1 mm
Basic dynamic load rating C	30.7 kN
Basic static load rating C ₀	23.2 kN
Fatigue load limit P _u	0.98 kN
Calculation factor k _r	0.025
Calculation factor f ₀	15.6
Mass bearing	0.43 kg