

# Timken 39236/39433 tapered roller bearings

Request A Quote 12 mm A1 For Your Special Timken 39236/39433 tapered roller bearings Needs Today! Free 37 mm A Quotes. ISO 9001 certified.

|    |          |
|----|----------|
| A  | 37 mm    |
| A1 | 12 mm    |
| A2 | 30 mm    |
| B  | 32 mm    |
| A5 | 23.5 mm  |
| d  | 36.51 mm |
| Dz | 80 mm    |
| G  | M6x1     |
| H  | 102 mm   |
| H1 | 89 mm    |
| H2 | 64 mm    |
| L  | 129 mm   |
| L1 | 78 mm    |
| L2 | 13 mm    |
| L3 | 64 mm    |
| N  | 22mm     |
| N1 | 16 mm    |
| N2 | 37 mm    |
| P  | 230 mm   |
| s1 | 16 mm    |
| S  | 8.5 mm   |
| SW | 3.97 mm  |

|   |               |
|---|---------------|
| Z   | 59.1 mm       |
| C   | 25.7 kN       |
| C0  | 15.2 kN       |
| T min.                                      | -40 °C        |
| T max.                                      | 100 °C        |
| Weight                                      | 1.58 kg       |
| Recommended tightening torque for set screw | 8 Nm          |
| Designation of housing                      | T207N-        |
| Designation of bearing                      | US207-23G2T04 |
| Designation of closed end cover             | SCC207        |
| Designation of open end cover               | SCOU207-23    |