

Timken 442-S/432 tapered roller bearings

What is Timken 442-S/432 tapered roller bearings in 37 mm A mechanical engineering? Manufacturing Service . Upload your CAD file for 12 mm A1 an instant. 30 mm A2

| | |
|----|----------|
| A | 37 mm |
| A1 | 12 mm |
| A2 | 30 mm |
| B | 42.9 mm |
| A5 | 25.4 mm |
| d | 33.34 mm |
| Dz | 80 mm |
| G | M6x1 |
| H | 102 mm |
| H1 | 89 mm |
| H2 | 64 mm |
| L | 129 mm |
| L1 | 78 mm |
| L2 | 13 mm |
| L3 | 64 mm |
| N | 22mm |
| N1 | 16 mm |
| N2 | 37 mm |
| s1 | 21.45 mm |
| S | 17.5 mm |
| SW | 3.97 mm |
| Z | 59.1 mm |

| | |
|---|--------------|
| C | 25.7 kN |
| C0 | 15.2 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Weight | 1.72 kg |
| Recommended tightening torque for set screw | 8 Nm |
| Designation of housing | T207N- |
| Designation of bearing | UC207-21G2L4 |
| Designation of closed end cover | SCC207 |
| Designation of open end cover | SCOU207-21 |