

# Timken 479/472X tapered roller bearings

What is the best 52 Outer Diameter (mm) place to 25x52x15.8 Size (mm) buy Timken 479/472X tapered roller bearings online? Manufacturing 25 Bore Diameter (mm) Service .

Size (mm)	25x52x15.8
Bore Diameter (mm)	25
Outer Diameter (mm)	52
Width (mm)	15,8
D	52 mm
d	25 mm
C	15.8 mm
B	16 mm
E	37 mm
F	30 mm
r1,2 – min.	0.3 mm
r3,4 – min.	0.3 mm
Basic dynamic load rating – C	16.5 kN
Basic static load rating – C0	22.8 kN
Fatigue load limit – Pu	2.7 kN
Maximum dynamic radial loads – Fr	18 kN
Maximum static radial loads – F0r	26 kN
Limiting speed	3400 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.177

Product Group	B04144
r1,2 min.	0.3 mm
r3,4 min.	0.3 mm
Basic dynamic load rating C	16.5 kN
Basic static load rating C0	22.8 kN
Fatigue load limit Pu	2.7 kN
Maximum dynamic radial load Fr max.	18 kN
Maximum static radial load F0r max.	26 kN
Mass support roller	0.18 kg